



ELESUN

ELESUN Coaxial Cable Product Information Sheet

Type:RG174LL-Foam Stranded 105°C

Series RG174LL Cable

Part Number:3RGS50ΩV00106

Stranded Bare Copper Clad Steel Conductor

Foam Polypropylene Dielectric

Laminate Aluminum Tape Shield

Tinned Copper Braid 90%

Black 105°C PVC Jacket



Structural parameters Information

Material	Detail	Size mm	Color
Inner Conductor	Copper Clad Steel (7Strand)	0.60	Coppery
Dielectric	Foam Polypropylene	1.60	Natural Color
1 st Outer Conductor	Laminate Aluminum Tape	1.65	Silvery
2 st Outer Conductor	90%Tinned-Copper Braid	2.05	Silvery
Jacket	PVC 105°C RoHS	3.00	Black

Physical Mechanical Specifications

Item	Unit	Date
Minimum Bend Radius	Loaded	20×Cable OD
	Unloaded	10×Cable OD
Static Operating Temperature, °C		-40~+105

Electrical Specifications

Item	Unit	Date
Impedance		50±3
Capacitance	pF/m	88
Velocity ratio Propagation	%	76
Resistance	Ω/km	
Inner Conductor		215
Outer Conductor		29.8

Attenuation,Maximum(20°C) (Permissible error±10%)

Frequency MHZ	dB/100m
50	15.9
100	21.7
500	48.9
1000	72.0
1500	89.3
1600	92.1
2000	103.7
2300	112.3
2500	118.1
3000	132.5
4000	157.5
5000	181.1
6000	202.4

JIANGSU ELESUN CABLE CO.,LTD.

Add:No.26,Shengyuan Road,Dantu New Town, Zhenjiang Tel:0511-8562351 Fax:0511-85632367 <http://www.cnals.com>